

Index

SO-08-0690

Index

Control button and jack entries as well as abbreviations such as SMPTE, MIDI and FM are in UPPER CASE.

A

American video frame rates, 4.4
ARPEGGIATE, 6.16
Arpeggiate, external, 6.16-18
Audio Event Editor
 digital transfer, 3.2-15
 MIDI locator, 7.36-37
 MIDI editing, 7.46-47, 7.49
 MIDI recording, 7.20
 routing, 2.8, 2.10-11
 setting time code
 parameters, 4.12-17
Audio synchronization, 5.2-3, 5.4-9
Audio-to-pulse signal conditioning, 6.2-7

B

BANK, 7.44-45
Beat mode synchronization, 5.2-3, 5.7

C

Channel messages, MIDI, 7.6
Channel pressure, 7.38, 7.50
Click
 external, 6.10-11
 track, external, 6.8-15
CLICK RATE, 6.10, 6.14-15
Coast, 4.10
Connectors
 Direct-to-Disk, 1.23-26
 Synclavier, 1.12-13
Controllers, real-time effects, 7.38-41
Cooling and ventilation
 Direct-to-Disk, 1.17
 Synclavier, 1.7
Copying
 Cue, digital transfer out, 3.11
Cuelists
 digital transfer out, 3.9-10
 routing, 2.8, 2.11-12
 volume, 2.13-14

D

Delay, sync, 6.7
Digital transfer
 connections, 3.3, 3.8
 Data light, 3.3
 delay, 3.2
 description, 3.2
 formats, 3.2-3, 3.6, 3.12
 hardware specifications, 3.16-32
 in, 3.12-14
 OFF button 3.2
 out, 3.6-11
 sampling rates, 3.4
 summary, 3.15
 Synchronization, 3.4, 3.6-8
 system slowdown, 3.2
 Word clock light, 3.3
Direct-to-Disk
 cuelist routing, 2.8
 inputs, 2.15-16
 track routing, 2.8-10
Display offset, 4.5, 4.15-16
Drop-frame SMPTE, 4.4
Drum replacement, 6.2-7

E

Editing MIDI messages, 7.46-50
ELCO 8016 120 pin connector, 1.20-21
ENTRY, 7.44-45
Equivalent times, 4.17
Erasing notes only, 7.31
European video frame rates, 4.4
Expression input controllers, 7.38-41
EXT SYNC MODE, 4.18, 5.4, 5.6, 5.9-10, 6.4, 6.7, 6.10, 6.12, 6.15, 6.17, 6.18, 7.18
External
 arpeggiate mode, 6.16-18
 repeat mode, 6.16-18
 synchronization signals, 5.2
 trigger mode, 6.12, 6.15
EXTERNAL CLOCK IN/OUT 5.3

F

Fifty Hz synchronization, 5.2-3, 5.4-6
Filtering MIDI real-time effects, 7.40-41
Footswitches, 1.14
FSK (frequency shift key) signals, 5.3, 6.5

G

Ground lift switch, 1.6

H

Hardware specifications, MIDI, 7.5
High speed clock signals, 5.10

I

Implementation chart, MIDI, 7.51
Individual pressure, 7.38, 7.50
INFO, 7.30
Input specifications
 Direct-to-Disk, 1.18
 Synclavier, 1.8
Input sources and channels, 2.15-16

J

K

Keyboard
 MIDI program change, 7.42-45
 routing, 2.3, 2.5
 volume, 2.6

L

Locator points, 7.36-37
Longitudinal time code, 4.7

M

- Maintenance, 1.2
- MARK, 7.35
- Meter bridge, 1.27
- MIDI
 - (button), 7.11-12, 7.13, 7.16, 7.18, 7.29, 7.43
 - controllers, 7.38-41
 - description, 7.2-9
 - devices, 7.2-3
 - Display (see MIDI Display)
 - distortion, 7.5
 - echo, 7.13
 - editing, 7.46-50
 - equipment, 7.2-3
 - hardware specifications, 7.5
 - implementation chart, 7.51
 - input parameters, 7.14-19
 - LOCATE, 7.36-37
 - mapping, 7.15-16
 - messages, 7.6-7, 7.38-50
 - multitrack recording and playback, 7.24-33
 - multitrack routing, 7.15-16
 - networks, 7.2-3
 - output parameters, 7.10-13
 - parameters, setting, 7.8
 - playback, 7.20, 7.23, 7.26, 7.33
 - ports, 7.4
 - program change, 7.42-45
 - real-time effects, 7.38-41
 - recording, 7.20, 7.22, 7.27-29, 7.32
 - saving parameters, 7.10-11, 7.14
 - sequence transfer, 7.24-32
 - signals, 7.5
 - song pointer, 7.7, 7.34-37
 - specifications, 7.2
 - synchronization, 7.13, 7.17-19
 - THRU box, 7.5
- MIDI Display
 - input channels, 7.14
 - outputs and channels, 7.10, 7.13
 - setting parameters, 7.8-9
- Multichannel Display
 - cuelist routing, 2.12
 - track routing, 2.4, 2.9
- Multichannel Distributor
 - description, 2.2
 - test, 2.2
- Multitrack
 - recording and playback, MIDI, 7.24-33
 - routing, MIDI, 7.15-16

N

O

- Offset
 - display, 4.5, 4.15-16
 - SMPTE, 4.5, 4.11, 4.13-14, 4.19
- Output specifications
 - Synclavier, 1.9, 1.11
 - Direct-to-Disk, 1.19

P

- Pan, 2.15
- Percussion replacement, 6.2-7
- Playback
 - cues with audio from more than one track, 2.13
 - MIDI, 7.20, 7.23, 7.26, 7.33
 - SMPTE, 4.22-23
- Power requirements
 - Direct-to-Disk, 1.16
 - Synclavier, 1.6
- Pressure, 7.10, 7.13, 7.22, 7.32, 7.38-39, 7.41, 7.50
- Program change, MIDI, 7.42-45
- Project Manager, routing, 2.8, 2.10-11
- Pulse signals, 5.2-3

Q

R

- Real-time effects, MIDI, 7.38-41
- Real-time effects controllers, 1.15
- Recorder Display, 7.46-48
- Recording
 - external click, 6.8-15
 - MIDI, 7.20, 7.22, 7.27-29, 7.32
 - sequence with SMPTE, 4.20-21
 - SMPTE time code, 4.25-27
- Repeat, external, 6.16-18
- REPEAT, 6.16
- REPEAT/ARPEGGIATE RATE, 6.17-18
- Resync, 4.10
- Retriggering function, 6.2

Routing

- cuelists, 2.8, 2.11-12
- Direct-to-Disk tracks, 2.8-10
- displays and panels, 2.8
- keyboard, 2.3, 2.5
- MIDI input channels, 7.15-16
- Multichannel Display, 2.4, 2.9
- notelists, 2.8
- Project Manager, 2.8, 2.10
- saved, 2.2
- sequencer tracks, 2.3-5
- stereo tracks, 2.3, 2.5
- Track Display, 2.10

S

- Saving (see also Storing) MIDI parameters, 7.10-11, 7.14
- Sequence Editor
 - assigning timbres, 7.25
 - entering numbers, 7.25
 - recording, 7.28
 - setting MIDI parameters, 7.8-9, 7.14-15
- Sequence transfer
 - digital, 3.2-31
 - MIDI, 7.26-32
- Servicing, 1.2
- Shipping and handling, 1.3
- Signal paths
 - Direct-to-Disk, 1.5
 - Synclavier, 1.4
- SKT, 7.12, 7.43
- SMPTE
 - coast, 4.10
 - equivalent times, 4.17
 - formats, 4.4
 - generating time code, 4.24-27
 - MODE, 4.18-19
 - offset, 4.5, 4.11, 4.13-14, 4.19
 - receiving, 4.6
 - recording time code, 4.24-27
 - recording with, 4.20-21
 - resync, 4.10
 - setting parameters, 4.12-17
 - storing parameters, 4.7
 - stripe recording, 4.25-27
 - synchronization, 4.2-27
 - time code, 4.2-4
 - turning off, 4.18

Index (con't)

- SMPTE playback
 - Direct-to-Disk, 4.23
 - keyboard control panel, 4.22
 - Sequence Editor, 4.22
 - SMPTE recording
 - Audio Event Editor, 4.21
 - Direct-to-Disk, 4.21
 - keyboard control panel, 4.20
 - Track Display, 4.22
 - SMPTE setup
 - Audio Event Editor, 4.12-17
 - keyboard control panel, 4.18-19
 - Sequence Editor, 4.8-11
 - SMT, 7.24-25
 - Song pointer, MIDI, 7.7, 7.34-37
 - Status, track, 7.30
 - Stereo routing, 2.3, 2.5
 - Sync delay, 6.7
 - Synchronization
 - audio tape, 5.2-3, 5.4-9
 - beat mode, 5.2-3, 5.7
 - delay, 6.7
 - digital transfer, 3.4, 3.6-8
 - drum replacement, 6.2-7
 - fifty Hz, 5.2-3, 5.4-6
 - FSK signals, 5.3
 - high speed clock signals, 5.10
 - MIDI, 7.13, 7.17-19
 - SMPTE, 4.2-16
 - to tape, 5.4-9
 - two systems, 5.10-11
 - Synchronization specifications
 - Direct-to-Disk, 1.22
 - Synclavier, 1.10
 - System messages, MIDI, 7.7
- T**
- Tape synchronization, 5.2-3, 5.4-9
 - Temperature, 1.4-5
 - Time code
 - longitudinal, 4.7
 - sampling rate, 1.38-39
 - SMPTE, 4.2-15
 - Vertical Interval (VITC), 4.7
- Track**
- blocking, 2.13
 - digital transfer out, 3.9-10
 - Display, 7.8-9
 - keyboard button
 - assignment, 7.8-9
 - output connector pin configuration, 1.34-35
 - output specifications, 1.32-35
 - routing, 2.2-10
 - splitting, 2.13
 - status, 7.30
 - volume, 2.7, 2.6
- Track Display, routing,**
2.8, 2.10
- TRACK ROUTING, 2.3, 2.5**
- TRACK VOLUME, 7.21**
- Transfer, digital (see Digital transfer)**
- Transferring sequences, 7.24-32**
- Trigger, external, 6.2, 6.4, 6.7, 6.12, 6.15**
- U**
- UDIO (*see* Digital transfer)
 - Universal Digital I/O (*see* Digital transfer)
- V**
- Ventilation, 1.4-5
 - Vertical Interval Time Code (VITC), 4.7
 - Volume
 - cuelist, 2.14
 - keyboard, 2.6
 - output, 2.14-15
 - track, 2.6-7
- W**
- X**
- Y**
- Z**